

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)


PCT

(10) International Publication Number
WO 2005/073682 A1

- (51) International Patent Classification⁷: **G01J 1/26**, H04N 5/335
- (74) Agent: LESICAR PERRIN; 49 Wright Street, Adelaide, SA 5000 (AU).
- (21) International Application Number: PCT/AU2005/000118
- (22) International Filing Date: 31 January 2005 (31.01.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2004900428 30 January 2004 (30.01.2004) AU
- (71) Applicant (for all designated States except US): **LASTEK LABORATORIES PTY LTD** [AU/AU]; Level 1, 205 Greenhill Road, Eastwood, South Australia 5063 (AU).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **STANCO, Alexei** [AU/AU]; 10 Reid Street, Thebarton, South Australia 5031 (AU). **AIZENGENDLER, Mark** [AU/AU]; 11 Warram Way, West Lakes Shore, South Australia 5020 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: A METHOD FOR PRODUCING HIGH SIGNAL TO NOISE SPECTRAL MEASUREMENTS IN OPTICAL DETECTOR ARRAYS



(57) Abstract: A method and apparatus are described for compensation of a dark current pattern in optical detector arrays, and in particular in uncooled linear CCD arrays. This is accomplished by providing a database (46) of dark signal readings unique to a particular detector (36), which can be used to correct a measured signal (40). The database (46) may comprise dark signal readings for each pixel, taken for a range of temperatures and exposure times, and may be created at the time of manufacture. The detector also includes a means (42) to measure its temperature, so that the appropriate dark signal values can be selected (or calculated via linear interpolation) from the database, and then subtracted from the measured signal.



Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.